



83" Tandem Axle Dump (D7)

D7



Lengths
10', 12', & 14'

Standard Features

- 9,990 lb. G.V.W.R.
- 5,200 lb. x 2 G.A.W.R.
- 2 5/16" Ball Adjustable Coupler
- Safety Chains
- 1 - Drop Leg Jack (7,000 lb.)
- 2 - Posi-lube Brake Axle (5,200 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 - 16" White Spoke Wheels
- 4 - 235/80R16 Radial Tires (3,520 lb.)
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- 1/8" Treadplate Steel Fenders
- Toolbox
- 2 - Way Gate (Barn Doors & Spread Gate)
- 6' 6" Slide In Channel Ramps
- 4 - D-Rings (Welded inside the Box)
- 40° Dump Pitch
- 12VDC Hydraulic Pump
- 5" x 30" Hydraulic Cylinder
- 14' Requires ScissorLift Option
- 12' Control Cable
- Mounting Brackets for Roll-up Tarp
- 6" Channel Main Frame & Tongue
- 2" x 6" x 11ga. Tubing Bed Frame
- 3" Channel Crossmembers 16" on Center
- 10ga. Steel Bed
- 83" Wide Bed
- 10ga. Steel Sides
- 24" High Sides
- DOT Approved Flushmount Lifetime LED Lights
- Sealed Wire Harness w/ 7-Way RV Plug
- Stake Pockets
- Sand Blasted, Acid Washed, Powder Coated
- Interstate (TM) Deep Cycle Battery



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams™ Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

Weights

Length	Axles	Est. Base Weight†
10'	2 - 5,200	3620 lbs / 1642 kg
12'	2 - 5,200	3820 lbs / 1733 kg
14'	2 - 7,000	4020 lbs / 1823 kg
14' Scissor	2- 7,000	4380 lbs / 1987 kg
14' Scissor/GN	2- 7,000	4960 lbs / 2250 kg

†Weights are estimated for base trailer only, PJ Trailers makes no guarantee regarding the accuracy of estimated weights



AIR RIDE SUSPENSION AVAILABLE



Also Available with a Gooseneck Coupler

Coupler Options

- BP 2 5/16" Adjustable (14,000 lb.) *
- Rigid mount 2-5/16 (25,000 lb.)
- GN Load-Leveling 2 5/16" Square (30,000 lb.)
- 3" Pintle Eye - Channel-mount (20,000 lb.)
- GN 2 5/16" Round (25,000 lb.)
- GN 2 5/16" Square (25,000 lb.)
- HD 2 5/16" Adj. Channel Mount 3 Bolt Coupler

Axle Options

- (2) 5,200# Electric / Spring *
- (2) 5,200# Hydraulic Drum / Spring
- (2) 5,200# Elec/Hyd Disk / Spring
- (2) 7,000# Electric / Spring
- (2) 7,000# Hydraulic Drum / Spring
- (2) 7,000# Elec/Hyd Disk / Spring
- (2) 7,000# Surge Disk / Spring
- (2) 7,000# Load Rg. G 14ply Tires Elec/Spring

Tail Options

- Split / Spreader Gate *

Color Options

- Black Powdercoat *
- Equipment Yellow Powdercoat
- Grey Powdercoat
- Red Powdercoat
- White Powdercoat

Other Options

- Cold Weather Wiring Harness (7-Way RV)
- 2nd Jack & Toolbox (GN Only)
- 10k Jack (Bumper Pull)
- Solar Battery Charger
- 6" Taller GN Riser
- 9,990 G.V.W.R.
- Battery Charger 12V
- Tarp Mounting Bracket
- 12"oc Crossmembers
- 1 Extra Pair of D-Rings
- HD 24" Side Extensions 10ga
- Mount Only for Spare Tire
- Tarp kit 18ft x 84 inchs (Pull Bar)
- Scissor Lift
- Spare Tire and Mount (Bumper Pull)
- Deck on the Neck (GN Only)
- 2-speed Jack (12,000 lb.)
- 24" Side Extensions (Solid)
- Grain Chute

Notes:

- 10' 5.12 cu yds
- 12' 6.14 cu yds
- 14' 7.17 cu yds

* denotes a standard feature